

ABC DOCKS



Aaron-Bradley Hydraulic Levelers

All Models - Standard Features - See Back for Options & Accessories

- Standard deck sizes, pit depths & dimensional requirements
- Deck & lip: High Strength Safety Tread Plate
- Service range: Up to +/- 12" from dock height
- Quiet hydraulic operation - No lifting required
- Automatic lip extension
- Lip keepers provide night lock security and cross traffic support
- Below dock safety; Maintenance strut
- Four inch lateral tilt for out of level trucks
- Full width, one-piece lip hinge pin
- Full operating range toe guards; welded design for maximum strength

'H' Series

- Structural 'C' Channel Deck Support
- Full Range Toe Guards
- Hydraulic Motor Pump w/ Rotary Switch Control
- Fully Hydraulic Deck and Lip
- Push-button Return to Dock
- Velocity Fuse, Fall Prevention
- Maintenance Strut
- Molded Bumpers, 2 ea



Actual product may vary from picture

Additional Models

'HD' Series

- Structural 'C' Channel Deck Support
- Full Range Toe Guards
- Push-button Control
- Auto Return to Dock
- Below Dock Control
- Molded Bumpers (2 ea)

'HX' Series

- Heavy Duty 'I-beam' or Box Beam Deck Support
- Full Range Toe Guards
- Push-button Control
- Independent Lip Control
- Emergency Stop
- Below Dock Control
- Auto Return to Dock

Specializing in Dock Equipment & Scissor Tables

ABC DOCKS



Aaron-Bradley Hydraulic Levelers

Options

- Lip Length: 18", 20"
- Weather Seals - Brush or Rubber
- Foam Insulation
- Abrasive Surface
- Pan, Self-forming w/ Leveler Welded In
- Laminated Bumpers
- Barrier Safety Lip
- 3 Wheel Forklift Reinforcement
- *Note: Options not available with all Series, call for details*

Accessories

- Curb Angle Kit
- Deep Pit Kit
- 'EZ' Pan (Assembled on Job Site)
- Free-Standing Frame
- *Note: Accessories not available with all Series, call for details*

Architectural Specifications

- Dock leveler (s) to be Aaron-Bradley Model _____. Standard unit to be ___' Wide x ___' Long. Unit to be hydraulic with continuous hinged lip and header plate design. Deck and lip to be 55,000 lbs. minimum yield steel tread plate.
- Deck support beam to be: () Structural Tubing ; () Structural 'I' beam or () Formed Beam or Channel .
- Lip to be ___" Long and extended ___" beyond bumpers. Rollover and cross traffic capacity to be _____ lbs. Leveler to automatically raise and extend lip when control button is activated. Lip to extend, lowering to floor of trailer.
- Leveler may be recycled and stored while truck is in position at dock.
- Levelers shall meet or exceed the performance requirements of O.S.H.A. CS202-56 (1910-30) "Other Walking Surfaces" and ANSI/MH30.1-2007 or most current revisions / publications in effect.

Warranty

- Starts from date of shipment - One (1) year standard on all units, unless otherwise noted.
- Option: ABC Docks will match any competitor's documented warranty for comparable products.

ABC Docks, LLC
P.O. Box 1028
Franklin, TN 37065-1028
Ph) 800-394-5944 / 615-371-1774
Fax) 615-371-1754

Distributed By:

Specializing in Dock Equipment & Scissor Tables