

# ABC DOCKS



## Aaron-Bradley Mechanical Levelers

### All Models - Standard Features - See Back for Options & Accessories

- Standard deck sizes, pit depths & dimensional requirements
- Deck & lip: High Strength Safety Tread Plate
- Service range: Up to +/- 12" from dock height
- Quiet operation - Easy pull chain operation - No lifting required
- Automatic lip extension
- Lip keepers provide night lock security and cross traffic support
- Below dock safety; Maintenance strut
- Four inch lateral tilt for out of level trucks
- Full width, one-piece lip hinge pin
- Working range toe guards; welded design for maximum strength

### **'M' & 'MX' Series**

- Rolled 'L' Beam or Structural 'C' Channel deck support beams
- Heavy duty Extension Spring design with easy front adjustment
- Grease Fittings on Lip Hinge
- Ratchet Hold-down with Auxiliary Release
- Dual Safety Legs
- Molded Bumpers, 2 ea



### Special Application

#### **'A' Series**

- Standard & Non-standard deck sizes and frame depths built to fit existing pits or special applications
- Construction specifics may vary depending upon the application
- Deck Support:
  - 25,000 lbs. - 35,000 lbs. Capacity, Formed Beam
  - 40,000 lbs. and greater, Structural 'I-beam'
- Bumpers, based on application requirements

**Specializing in Dock Equipment & Scissor Tables**

# ABC DOCKS



## Aaron-Bradley Mechanical Levelers

### Options

- Lip Length: 18", 20"
- Full Operating Range Toe Guard
- Weather Seals - Brush or Rubber
- Foam Insulation
- Abrasive Surface
- Pan, Self-forming w/ Leveler Welded In
- Laminated Bumpers
- Yieldable Lip - 'M' Series (Not available on 'A')
- Barrier Safety Lip - ('A' and 'MX' only)
- 3 Wheel Forklift Reinforcement - ('A' and 'MX' only)
- *Note: Options are not available with all Series, call for details.*

### Accessories

- Curb Angle Kit
- Deep Pit Kit
- 'EZ' Pan (Assembled on Job Site)
- Free-Standing Frame
- *Note: Accessories are not available with all Series, call for details.*

### Architectural Specifications

- Dock leveler (s) to be Aaron-Bradley Model \_\_\_\_\_. Standard unit to be \_\_\_' Wide x \_\_\_' Long. Unit to be mechanical with continuous hinged lip and header plate design. Deck and lip to be 55,000 lbs. minimum yield steel tread plate.
- Deck support beam to be: ( ) Structural Tubing ; ( ) Structural 'I' beam or ( ) Formed Beam or Channel .
- Lip to be \_\_\_" Long and extended \_\_\_" beyond bumpers. Rollover and cross traffic capacity to be \_\_\_\_\_ lbs. Leveler to automatically raise and extend lip when chain release is pulled. Lip to lock in position when extended and unit is walked down to rest position on trailer floor.
- Optional Yieldable Lip available with 'M' Series only. Will yield to impact and release.
- Leveler lip may be recycled and stored while truck is in position at dock.
- Positive hold down device.
- Levelers shall meet or exceed the performance requirements of O.S.H.A. CS202-56 (1910-30) "Other Walking Surfaces" and ANSI/MH30.1-2007 or most current revisions / publications in effect.

### Warranty

- Starts from date of shipment - One (1) year standard on all units, unless otherwise noted.
- Option: ABC Docks will match any competitor's documented warranty for comparable products.

**ABC Docks, LLC**  
**P.O. Box 1028**  
**Franklin, TN 37065-1028**  
**Ph) 800-394-5944 / 615-807-1141**  
**Fax) 615-807-1752**

**Distributed By:**

**Specializing in Dock Equipment & Scissor Tables**