



Note: If the shelter is incorrectly specified and / or misapplied for the application, not only will the unit be ineffective, but it may also result in damage to the building and / or the shelter. This unit requires a minimum height of 15' 0" off grade.

**Site Criteria Data:**

A. Door Width \_\_\_\_\_" B. Door Height \_\_\_\_\_" C. Distance to Overhead Structure (If Applicable) \_\_\_\_\_"  
 D. Bumper Projection \_\_\_\_\_" + ( Wall Setback \_\_\_\_\_" ) or - ( Wall projection \_\_\_\_\_" ) = Total Bumper Projection \_\_\_\_\_"  
**Dock Approach:**  Level  Decline  Incline % Grade \_\_\_\_\_ ( Length \_\_\_\_\_" ) **RX.** Dock Height \_\_\_\_\_"

**Shelter Data:** (Note: Head frame requires an additional 4" above the top of the side pads.)

E. Top Projection \_\_\_\_\_" F. Bottom Projection \_\_\_\_\_" G. Overall Unit Width \_\_\_\_\_"  
 H. Overall Unit Height \_\_\_\_\_" J. Head Curtain Height \_\_\_\_\_" K. Side Pad Width \_\_\_\_\_"

**Head Curtain Options:**

Flame Retardant Fabric (Black Only)  40oz Vinyl  22oz Vinyl  
 Curtain Style Header  Specify Curtain Height \_\_\_\_\_"  Specify Curtain Split Height \_\_\_\_\_"

**Side Curtain Data:**

M. Left Side Curtain Width \_\_\_\_\_" N. Right Side Curtain Width \_\_\_\_\_" O. Side Curtain Length \_\_\_\_\_"

**Options:**

Flame Retardant Foam  Flame Retardant Fabric (Black Only)  40oz Vinyl  22oz Vinyl

**Fabric Data:** (\*Note: Blue, Brown and Green available in 22oz or 40oz Vinyl only)

Fabric  50oz AB500  40oz Vinyl (standard)  22oz Vinyl

Color Selection \* (select one):  Black (standard)  Blue  Brown  Green

**Trailer Service Range:**

Maximum Height of Trailer(s) Serviced \_\_\_\_\_" Minimum Height of Trailer(s) Serviced \_\_\_\_\_"

**Project Data:**

Quantity \_\_\_\_ Customer/Job Name \_\_\_\_\_ Approved \_\_\_\_\_ Date \_\_\_\_\_